


Reach-In Unit Coolers Series




MU MULLION - Above +34°F

- Economical thin-line design allows maximum product storage space reach-ins and beverage coolers.
- Designed for easy mounting on the backwall, at either end of the cooler or behind the mullion.
- Special air flow configuration draws air at the top and discharges at the bottom on one or both sides.
- Sufficient room to mount thermal expansion valve.
- Heavy gauge aluminum housings with stainless steel screws and rust-resistant hardware.
- Dependable, heavy-duty fan motors with thermal overload protection.

MU MULLION PERFORMANCE DATA

| MODEL | CAPACITY (BTU/h) | | CFM | MOTORS | | FAN DIA (IN) | UNIT SIZE (IN) | | | CONNECTIONS (IN) | | R-404A R-507 CHARGE @ 30% (LBS) | SHIPPING WEIGHT (LBS) |
|--------|------------------|----------|-----|--------|-----|--------------|----------------|--------|-------|------------------|-----------|---------------------------------|-----------------------|
| | 10° F TD | 15° F TD | | QTY | AMP | | LENGTH | HEIGHT | DEPTH | LIQ F.N. | SUCT O.D. | | |
| MU-135 | 1350 | 2025 | 210 | 2 | 1.2 | 5 | 15-5/8 | 18-3/4 | 5-1/2 | 1/2 | 3/8 | 0.4 | 14 |
| MU-165 | 1650 | 2475 | 180 | 2 | 1.2 | 5 | 15-5/8 | 18-3/4 | 5-1/2 | 1/2 | 3/8 | 0.6 | 16 |
| MU-235 | 2350 | 3525 | 270 | 3 | 1.8 | 5 | 22 | 18-3/4 | 5-1/2 | 1/2 | 1/2 | 0.9 | 22 |



SX SPACE SAVER - Above +34°F

- Compact design from optimum storage space.
- Optional ceiling or backwall mounting reduces door sweating.
- Heavy gauge aluminum housings with stainless steel screws and rust-resistant hardware.
- Dependable, heavy-duty fan motors with thermal overload protection.
- Rugged thermoplastic fan blades and guards.

SX SPACE SAVER PERFORMANCE DATA

| MODEL | CAPACITY (BTU/h) | | CFM | MOTORS | | FAN DIA (IN) | UNIT SIZE (IN) | | | CONNECTIONS (IN) | | R-404A R-507 CHARGE @ 30% (LBS) | SHIPPING WEIGHT (LBS) |
|--------|------------------|----------|-----|--------|-----|--------------|----------------|--------|-------|------------------|-----------|---------------------------------|-----------------------|
| | 10° F TD | 15° F TD | | QTY | AMP | | LENGTH | HEIGHT | DEPTH | LIQ F.N. | SUCT O.D. | | |
| SX-70 | 700 | 1050 | 160 | 1 | 0.7 | 5 | 14-3/8 | 6-7/8 | 7-7/8 | 3/8 | 1/2 | 0.2 | 6 |
| SX-95 | 950 | 1430 | 150 | 1 | 0.7 | 5 | 14-3/8 | 6-7/8 | 7-7/8 | 3/8 | 1/2 | 0.3 | 7 |
| SX-110 | 1100 | 1650 | 250 | 1 | 0.7 | 6 | 17-3/8 | 7-7/8 | 7-7/8 | 3/8 | 1/2 | 0.3 | 8 |
| SX-140 | 1400 | 2100 | 240 | 1 | 0.7 | 6 | 17-3/8 | 7-7/8 | 7-7/8 | 3/8 | 1/2 | 0.5 | 9 |



DF DUAL FLOW - Above +34°F

- Ideal for reach-ins, back bars, beverage coolers and similar applications.
- Dual coil unit mounts to the ceiling, delivers uniform, two-sided discharge and increased circulation within the cooler (Model DF-70 has single coil and single-sided air discharge).
- Sufficient room to mount thermal expansion valve.
- Heavy gauge aluminum housings with stainless steel screws and rust-resistant hardware.
- Die-formed fan venturi is quiet, delivers optimum air circulation.
- Dependable, heavy-duty fan motors with thermal overload protection.

DF DUAL FLOW PERFORMANCE DATA

| MODEL | CAPACITY (BTU/h) | | CFM | MOTORS | | FAN DIA (IN) | UNIT SIZE (IN) | | | CONNECTIONS (IN) | | R-404A (1) R-507 CHARGE @ 30% (LBS) | SHIPPING WEIGHT (LBS) |
|--------|------------------|----------|-----|--------|-----|--------------|----------------|--------|--------|------------------|-----------|-------------------------------------|-----------------------|
| | 10° F TD | 15° F TD | | QTY | AMP | | LENGTH | HEIGHT | DEPTH | LIQ F.N. | SUCT O.D. | | |
| DF-70 | 700 | 1050 | 100 | 1 | 0.5 | 6 | 15-3/8 | 4-3/8 | 9-7/8 | 1/4 O.D. | 3/8 | 0.3 | 7 |
| DF-90 | 900 | 1350 | 150 | 1 | 0.5 | 6 | 19-1/2 | 14-3/4 | 14-3/8 | 1/2 F.N. | 3/8 | 0.3 | 11 |
| DF-110 | 1100 | 1650 | 140 | 1 | 0.5 | 6 | 19-1/2 | 14-3/4 | 14-3/8 | 1/2 F.N. | 3/8 | 0.4 | 12 |
| DF-130 | 1300 | 1950 | 220 | 1 | 0.5 | 8 | 19-1/2 | 14-3/4 | 14-3/8 | 1/2 F.N. | 3/8 | 0.4 | 12 |
| DF-150 | 1500 | 2250 | 185 | 1 | 0.5 | 8 | 19-1/2 | 14-3/4 | 14-3/8 | 1/2 F.N. | 3/8 | 0.6 | 12 |
| DF-180 | 1800 | 2700 | 210 | 1 | 0.6 | 8 | 19-1/2 | 14-3/4 | 14-3/8 | 1/2 F.N. | 3/8 | 0.7 | 13 |
| DF-230 | 2300 | 3450 | 310 | 1 | 0.6 | 8 | 22-1/2 | 5-3/4 | 17-5/8 | 1/2 F.N. | 3/8 | 0.9 | 15 |
| DF-300 | 3000 | 4500 | 410 | 1 | 0.6 | 10 | 22-1/2 | 5-3/4 | 17-5/8 | 1/2 F.N. | 3/8 | 1.1 | 16 |

Internally equalized expansion valve operation. All unit electricals are 120/1/60. All drain connectors are 1/2" O.D. (1) Multiply by 1.1 for R-22 refrigerant.