



KR-A2L Series

COMPACT EVAPORATORS / UNIT COOLERS




ADVANTAGES

- A2Ls are synthetic, mildly flammable refrigerants that meet low GWP regulatory requirements and offer the greatest ease of use for technicians compared to other solutions
- Swept wing fan blade design provides low noise operation
- Variable speed motors for maximum efficiency
- Included coil guard(s) provide an additional layer of protection from accidental damage



KEY FEATURES

- Hinged front access to refrigeration and electrical components for easy access and service
- Standard non-metallic fan guards eliminate the possibility of corrosion
- Coil constructed of heavy-wall copper tube and rippled full collar aluminum fins—optional coil coating available
- Die-formed patterned aluminum cabinet and drain pan with easy-to-clean radius corners
- Factory-wired fans and defrost controls to terminal blocks for convenient field connections
- Built-in refrigerant leak detection system
- Includes required *ship loose* check valve and safety shut-off valve for field installation
- DOE/NRCan compliant



KRD2 shown



1.800.922.1919



www.krack.com

KR-A2L Compact Evaporators / Unit Coolers

SPECIFICATIONS

Model	KR-A2L	
Available Refrigerant Configurations	A2L (R-454A or R-454C)	
Power Connection	Field-Wired	
Supply Power	Motor	120 VAC / 1-phase / 60 Hz 208 VAC / 1-phase / 60 Hz
	Heater	120 VAC / 1-phase / 60 Hz 208 VAC / 1-phase / 60 Hz 208 VAC / 3-phase / 60 Hz

TECHNICAL INFORMATION




Scan or click QR to access additional resources at krack.com

AVAILABLE CONFIGURATIONS

- Air, electric, or gas defrost
- Choice of refrigerant compatibility (R-454A or R-454C)
- 1-6 fans to accommodate various loads

DIMENSIONS



Model	A	B	C (Length)	D
KRD1 (1-fan)	N/A	18 (457)	29 1/8 (740)	14 1/2 (368)
KRD2 (2-fan)	N/A	36 (914)	47 1/8 (1,197)	23 1/2 (597)
KRD3 (3-fan)	N/A	54 (1,372)	65 1/8 (1,654)	32 1/2 (826)
KRD4 (4-fan)	36 (914)	72 (1,829)	83 1/8 (2,111)	41 1/2 (1,054)
KRD5 (5-fan)	45 (1,143)	90 (2,286)	101 1/8 (2,569)	50 1/2 (1,283)
KRD6 (6-fan)	54 (1,372)	108 (2,743)	119 1/8 (3,026)	59 1/2 (1,511)

NOTE: Please see unit datasheet for information related to Minimum Room Floor Area requirements.

NOTE: Dimensions are in Inches (millimeters)

NOTE: Use Krack's technical data sheets to get dimensions for all store layout purposes.

We reserve the right to change or revise specifications and product design in connection with any feature of our products. Such changes do not entitle the buyer to corresponding changes, improvements, additions, or replacements for equipment previously sold or shipped. For additional resources, contact your representative or visit www.hussmann.com.



Krack, a Hussmann Corporation brand

For all customers inquiries, visit www.krack.com or call 1.800.922.1919

www.krack.com
www.hussmann.com